

M	HSS	HSS-E	DIN 376	ISO 2-6H	ISO 6HX
---	-----	-------	---------	----------	---------









Filettatura metrica ISO DIN 13			passo grosso													
						Anello rosso	Anello verde	Anello rosso Nitruato	Anello verde	Anello viola Vaporizzato	Nitruato					
			F 7863/3	F 7863/4	F 7865/3	F 7865/4	F 7865/5	F 7868	F 7871							
Modello			6245 Grulo-Spez.-R	6345 Grulo-Spez.-G	7255 Rapid-Spez.-R	7275 Rapid-VA-G	7235 Rapid V4A	6008 C-GG	6044 Grulo-Alu							
DIN			376	376	376	376	376	376	376							
Esecuzione/Forma			C/Elica destra 40°	C/Elica destra 40°	B/Imbocco corretto	B/Imbocco corretto	C/Imbocco corretto	C/Nitruati	C/Elica destra 45°							
Acciaio			HSS-E	HSS-E	HSS-E	HSS-E	HSS-E	HSS-E	HSS-E							
Tolleranza			ISO 2-6H	ISO 2-6H	ISO 2-6H	ISO 2-6H	ISO 6HX	ISO 6HX	ISO 6HX							
Per fori																
Per materiali gruppo:			1.3.1 - 1.3.2 5.1	1.4 - 1.6 3.1 - 3.2.1	1.3.1 - 1.3.2 5.1	1.2 - 1.4 - 1.6 3.1 - 3.2.1	1.4 - 1.5 - 1.6 3.2.12.1 - 2.2	2.1 - 2.2	3.1							
M	Passo mm	Tagliente mm	Codice F 7863	Cad. €	Codice F 7863	Cad. €	Codice F 7865	Cad. €	Codice F 7865	Cad. €	Codice F 7865	Cad. €	Codice F 7868	Cad. €	Codice F 7871	Cad. €
4	0,7	3,30	—	—	4004	—	—	—	—	—	—	—	—	—	—	—
5	0,8	4,20	—	—	4005	—	—	—	—	—	—	—	—	—	—	—
6	1	5,00	3006	—	4006	—	—	4006	—	—	—	—	—	—	—	—
8	1,25	6,80	3008	—	4008	—	—	4008	—	—	—	0008	—	0008	—	—
10	1,5	8,50	3010	—	4010	—	3010	4010	—	—	—	0010	—	0010	—	—
12	1,75	10,20	3012	—	4012	—	3012	4012	—	5012	—	0012	—	—	—	—
14	2	12,00	3014	—	4014	—	3014	4014	—	5014	—	—	—	0014	—	—
16	2	14,00	3016	—	4016	—	3016	4016	—	5016	—	0016	—	—	—	—
18	2,5	15,50	3018	—	—	—	3018	4018	—	—	—	0018	—	0018	—	—
20	2,5	17,50	3020	—	—	—	3020	4020	—	—	—	—	—	—	—	—
22	2,5	19,50	—	—	—	—	—	4022	—	—	—	0022	—	0022	—	—
24	3	21,00	—	—	—	—	—	—	—	—	—	—	—	0024	—	—
27	3	24,00	—	—	—	—	—	—	—	—	—	0027	—	—	—	—

Tabella per la scelta dei maschi e indicazioni sui rivestimenti, vedere pag. 552÷555